




Analysis Sector Orientation 4.2

<i>Author</i>	<i>Kalyan Jinnuri</i>
<i>Subject</i>	<i>Hinge A constrained in XZ and Hinge B & Nose Constrained in YZ</i>
<i>Prepared for</i>	<i>Region 3 Drift Chamber Design</i>
<i>First Saved</i>	<i>Thursday, May 01, 2008</i>
<i>Last Saved</i>	<i>Thursday, May 01, 2008</i>
<i>Product Version</i>	<i>11.0 Release</i>



Contents

- **Orientation 4.1**
 - [Geometry](#)
 - [Parts](#)
 - [Connections](#)
 - [Contact Regions](#)
 - [Mesh](#)
 - **Static Structural**
 - [Analysis Settings](#)
 - [Acceleration](#)
 - [Loads](#)
 - [Solution](#)
 - [Solution Information](#)
 - [Results](#)
- **Material Data**
 - [Aluminum](#)
 - [Polyurethane](#)
 - [Stainless Steel](#)
 - [Carbon Fiber](#)
 - [Hexcel](#)

Units

TABLE 1

Unit System	Metric (mm, kg, N, °C, s, mV, mA)
Angle	Degrees
Rotational Velocity	rad/s

Orientation 4.1

Geometry

TABLE 2
Orientation 4.1 > Geometry

Object Name	<i>Geometry</i>
State	Fully Defined
Definition	
Source	C:\Documents and Settings\Jinnuri\Desktop\website\R3_2.agdb
Type	DesignModeler
Length Unit	Millimeters
Element Control	Program Controlled
Display Style	Part Color
Bounding Box	
Length X	4768.3 mm
Length Y	4317.7 mm
Length Z	2060. mm
Properties	
Volume	8.52e+008 mm ³

Mass	342.76 kg
Statistics	
Bodies	29
Active Bodies	29
Nodes	160363
Elements	26466
Preferences	
Import Solid Bodies	Yes
Import Surface Bodies	Yes
Import Line Bodies	Yes
Parameter Processing	Yes
Personal Parameter Key	DS
CAD Attribute Transfer	No
Named Selection Processing	No
Material Properties Transfer	No
CAD Associativity	Yes
Import Coordinate Systems	No
Reader Save Part File	No
Import Using Instances	Yes
Do Smart Update	No
Attach File Via Temp File	No
Analysis Type	3-D
Mixed Import Resolution	None
Enclosure and Symmetry Processing	Yes

TABLE 3
Orientation 4.1 > Geometry > Parts

Object Name	<i>Nose Plate</i>	<i>Left Endplate Downstream Hole area</i>	<i>Right Endplate Upstream Hole area</i>	<i>Left Endplate Upstream Hole area</i>	<i>Left Endplate Aluminum Casing</i>
State	Meshed				
Graphics Properties					
Visible	Yes				
Transparency	1				
Definition					
Suppressed	No				
Material	Aluminum	Polyurethane			Aluminum
Stiffness Behavior	Flexible				
Nonlinear Material Effects	Yes				
Bounding Box					
Length X	180.6 mm	2159.8 mm	2116.2 mm	1973.8 mm	2338.9 mm
Length Y	94.006 mm	3690. mm	3614.6 mm	3368. mm	4000.3 mm
Length Z	529.95 mm	1562.8 mm	1531.7 mm	1437.5 mm	1983.2 mm
Properties					
Volume	6.6319e+006 mm ³	4.3107e+007 mm ³	4.1332e+007 mm ³	3.8462e+007 mm ³	1.1673e+007 mm ³
Mass	17.906 kg	10.346 kg	9.9198 kg	9.2309 kg	31.518 kg
Centroid X	-1.8724e-016 mm	-1157.7 mm	1145.5 mm	-1057.2 mm	-1178.2 mm
Centroid Y	42.65 mm	1932.5 mm	1911.3 mm	1758.4 mm	1967.9 mm

Centroid Z	-263.29 mm	368. mm	587.1 mm	528.73 mm	639.08 mm
Moment of Inertia Ip1	4.2714e+005 kg·mm ²	1.68e+007 kg·mm ²	1.5457e+007 kg·mm ²	1.2459e+007 kg·mm ²	5.6821e+007 kg·mm ²
Moment of Inertia Ip2	4.4442e+005 kg·mm ²	34145 kg·mm ²	31455 kg·mm ²	29271 kg·mm ²	1.6143e+006 kg·mm ²
Moment of Inertia Ip3	43603 kg·mm ²	1.677e+007 kg·mm ²	1.543e+007 kg·mm ²	1.2434e+007 kg·mm ²	5.5221e+007 kg·mm ²
Statistics					
Nodes	440	296	272	2445	
Elements	179	24	22	926	

TABLE 4
Orientation 4.1 > Geometry > Parts

Object Name	<i>Left Endplate Polyurethane</i>	<i>Right Endplate Downstream Hole area</i>	<i>Right Endplate Aluminum Casing</i>	<i>Right Endplate Polyurethane</i>	<i>Left Endplate Inner Steel slice</i>
State	Meshed				
Graphics Properties					
Visible	Yes				
Transparency	1				
Definition					
Suppressed	No				
Material	Polyurethane		Aluminum	Polyurethane	Stainless Steel
Stiffness Behavior	Flexible				
Nonlinear Material Effects	Yes				
Thickness					
Thickness Mode	Manual				
Bounding Box					
Length X	2327.6 mm	1998.1 mm	2338.8 mm	2322.8 mm	2294.9 mm
Length Y	3980.8 mm	3410. mm	4000.2 mm	3972.4 mm	3974.9 mm
Length Z	1956.7 mm	1457.6 mm	1984. mm	1954.5 mm	1983.2 mm
Properties					
Volume	3.4557e+007 mm ³	3.9784e+007 mm ³	1.1919e+007 mm ³	3.4764e+007 mm ³	2.9149e+006 mm ³
Mass	8.2936 kg	9.5482 kg	32.181 kg	8.3434 kg	23.319 kg
Centroid X	-1396. mm	1078.8 mm	1201.6 mm	1379.8 mm	
Centroid Y	2345.1 mm	1795.8 mm	2008.4 mm	2317.1 mm	
Centroid Z	542.67 mm	316.67 mm	651.27 mm	513.21 mm	
Moment of Inertia Ip1	2.0961e+007 kg·mm ²	1.321e+007 kg·mm ²	6.0236e+007 kg·mm ²	2.1346e+007 kg·mm ²	
Moment of Inertia Ip2	2.0417e+005 kg·mm ²	31513 kg·mm ²	1.6548e+006 kg·mm ²	1.8581e+005 kg·mm ²	
Moment of Inertia Ip3	2.076e+007 kg·mm ²	1.3183e+007 kg·mm ²	5.8594e+007 kg·mm ²	2.1163e+007 kg·mm ²	
Surface Area (approx.)					
	2.3908e+006 mm ²				
Statistics					
Nodes	1862	272	2379	1843	168
Elements	639	22	905	627	124

TABLE 5

Orientation 4.1 > Geometry > Parts

Object Name	<i>Left Endplate Outer Steel slice</i>	<i>Right Endplate Outer Steel slice</i>	<i>Right Endplate Inner Steel Slice</i>	<i>Backplate Aluminum Casing</i>	<i>Backplate Polyurethane</i>
State	Meshed				
Graphics Properties					
Visible	Yes				
Transparency	1				
Definition					
Suppressed	No				
Material	Stainless Steel			Aluminum	Polyurethane
Nonlinear Material Effects	Yes				
Thickness	1.2192 mm				
Thickness Mode	Manual				
Stiffness Behavior				Flexible	
Bounding Box					
Length X	2294.9 mm	2294.8 mm		4682.7 mm	4659.3 mm
Length Y	3974.9 mm	3974.8 mm		186.53 mm	180.41 mm
Length Z	1983.2 mm	1984. mm		498.46 mm	476.92 mm
Properties					
Volume	2.9149e+006 mm ³			5.2863e+006 mm ³	1.1124e+008 mm ³
Mass	23.319 kg			14.273 kg	26.698 kg
Surface Area (approx.)	2.3908e+006 mm ²				
Centroid X				175.74 mm	-0.24556 mm
Centroid Y				3986.6 mm	3987.5 mm
Centroid Z				1225.6 mm	1222.4 mm
Moment of Inertia Ip1				7.8718e+005 kg·mm ²	5.1362e+005 kg·mm ²
Moment of Inertia Ip2				3.0219e+007 kg·mm ²	4.725e+007 kg·mm ²
Moment of Inertia Ip3				2.9438e+007 kg·mm ²	4.6748e+007 kg·mm ²
Statistics					
Nodes	176	157	155	708	241
Elements	132	113	111	74	24

TABLE 6
Orientation 4.1 > Geometry > Parts

Object Name	<i>Backplate Outer steel slice</i>	<i>Back Plate Inner Steel slice</i>	<i>Rod 4</i>	<i>Rod 5</i>	<i>Rod 6</i>
State	Meshed				
Graphics Properties					
Visible	Yes				
Transparency	1				
Definition					
Suppressed	No				
Material	Stainless Steel		Carbon Fiber		
Nonlinear Material Effects	Yes				

Thickness	1.2192 mm				
Thickness Mode	Manual				
Stiffness Behavior			Flexible		
Bounding Box					
Length X	4524.4 mm	2618.1 mm	3260.4 mm	3902.6 mm	
Length Y	137.65 mm	50.8 mm			
Length Z	484.52 mm	50.8 mm			
Properties					
Volume	2.7483e+006 mm ³	5.1151e+005 mm ³	6.3841e+005 mm ³	7.6532e+005 mm ³	
Mass	21.987 kg	0.29667 kg	0.37028 kg	0.44388 kg	
Surface Area (approx.)	2.2542e+006 mm ²				
Centroid X		-3.0688e-010 mm	-8.6731e-011 mm	-1.3795e-008 mm	
Centroid Y		2220.1 mm	2776.3 mm	3332.5 mm	
Centroid Z		880.31 mm	1091.6 mm	1302.9 mm	
Moment of Inertia Ip1		177.84 kg·mm ²	221.97 kg·mm ²	266.09 kg·mm ²	
Moment of Inertia Ip2		1.6387e+005 kg·mm ²	3.1853e+005 kg·mm ²	5.4867e+005 kg·mm ²	
Moment of Inertia Ip3		1.6388e+005 kg·mm ²	3.1853e+005 kg·mm ²	5.4867e+005 kg·mm ²	
Statistics					
Nodes	174	186	27520	34352	41184
Elements	129	141	3920	4896	5872

TABLE 7
Orientation 4.1 > Geometry > Parts

Object Name	<i>Rod 1</i>	<i>Rod 2</i>	<i>Rod 3</i>	<i>Force ref line</i>	<i>30 deg Ref line</i>
State	Meshed				
Graphics Properties					
Visible	Yes				
Transparency	1				
Definition					
Suppressed	No				
Material	Carbon Fiber		Aluminum		
Stiffness Behavior	Flexible				
Nonlinear Material Effects	Yes				
Bounding Box					
Length X	691.28 mm	1333.5 mm	1975.8 mm	70. mm	11.116 mm
Length Y	50.8 mm		3.6786 mm		19.253 mm
Length Z	50.8 mm		5. mm		
Properties					
Volume	1.3079e+005 mm ³	2.577e+005 mm ³	3.846e+005 mm ³	643.76 mm ³	535.05 mm ³
Mass	7.586e-002 kg	0.14946 kg	0.22307 kg	1.7382e-003 kg	1.4446e-003 kg
Centroid X	-7.386e-011 mm	5.0812e-010 mm	-5.8382e-011 mm	2.7078e-014 mm	-3.7053 mm
Centroid Y	551.82 mm	1107.8 mm	1663.9 mm	68.426 mm	39.079 mm
Centroid Z	246.45 mm	457.74 mm	669.03 mm	2.5 mm	

Moment of Inertia Ip1	45.457 kg·mm ²	89.595 kg·mm ²	133.72 kg·mm ²	4.9279e-003 kg·mm ²	3.5962e-002 kg·mm ²
Moment of Inertia Ip2	2768.1 kg·mm ²	21001 kg·mm ²	69702 kg·mm ²	0.3585 kg·mm ²	9.7246e-003 kg·mm ²
Moment of Inertia Ip3	2768.2 kg·mm ²	21001 kg·mm ²	69702 kg·mm ²	0.35618 kg·mm ²	3.9668e-002 kg·mm ²
Statistics					
Nodes	11946	7788	20576	237	294
Elements	1760	1104	2928	22	38

TABLE 8
Orientation 4.1 > Geometry > Parts

Object Name	<i>60 Deg Ref line</i>	<i>Left Hinge</i>	<i>Right Hinge</i>	<i>Hexcel</i>
State	Meshed			
Graphics Properties				
Visible	Yes			
Transparency	1			
Definition				
Suppressed	No			
Material	Aluminum	Polyurethane	Hexcel	
Stiffness Behavior	Flexible			
Nonlinear Material Effects	Yes			
Bounding Box				
Length X	20.123 mm	250.37 mm	4671.1 mm	
Length Y	11.618 mm	371.11 mm	3939.1 mm	
Length Z	5. mm	528.13 mm	1527.6 mm	
Properties				
Volume	584.49 mm ³	2.9863e+007 mm ³	3.9367e+008 mm ³	
Mass	1.5781e-003 kg	7.1671 kg	11.351 kg	
Centroid X	-6.7077 mm	-1527.6 mm	1521.8 mm	-2.4337e-006 mm
Centroid Y	13.673 mm	4131.5 mm	4132.1 mm	2672.3 mm
Centroid Z	2.5 mm	1265.9 mm	1263.7 mm	485.69 mm
Moment of Inertia Ip1	1.1301e-002 kg·mm ²	1.7368e+005 kg·mm ²	1.1729e+007 kg·mm ²	
Moment of Inertia Ip2	4.2611e-002 kg·mm ²	1.7368e+005 kg·mm ²	1.0294e+007 kg·mm ²	
Moment of Inertia Ip3	4.7337e-002 kg·mm ²	74658 kg·mm ²	2.2019e+007 kg·mm ²	
Statistics				
Nodes	250	376	3394	
Elements	30	54	1572	

Connections

TABLE 9
Orientation 4.1 > Connections

Object Name	<i>Connections</i>
State	Fully Defined
Auto Detection	
Generate Contact On Update	Yes
Tolerance Type	Slider
Tolerance Slider	0.
Tolerance Value	16.886 mm
Face/Face	Yes

Face/Edge	No
Edge/Edge	No
Priority	Include All
Same Body Grouping	Yes
Revolute Joints	Yes
Fixed Joints	Yes
Transparency	
Enabled	Yes

TABLE 10
Orientation 4.1 > Connections > Contact Regions

Object Name	Contact Region	Contact Region 2	Contact Region 3	Contact Region 4	Contact Region 5
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	2 Faces				1 Face
Target	2 Faces				1 Face
Contact Bodies	Nose Plate				
Target Bodies	Left Endplate Aluminum Casing	Left Endplate Polyurethane	Right Endplate Aluminum Casing	Right Endplate Polyurethane	Left Endplate Inner Steel slice
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				
Normal Stiffness	Program Controlled				
Update Stiffness	Never				
Thermal Conductance	Program Controlled				
Pinball Region	Program Controlled				

TABLE 11
Orientation 4.1 > Connections > Contact Regions

Object Name	Contact Region 6	Contact Region 7	Contact Region 8	Contact Region 9	Contact Region 10
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face				4 Faces
Target	1 Face				4 Faces
Contact Bodies	Nose Plate				Left Endplate Downstream Hole area
Target Bodies	Right Endplate Inner Steel Slice	Force ref line	30 deg Ref line	60 Deg Ref line	Left Endplate Polyurethane
Definition					
Type	Bonded				
Scope Mode	Automatic				

Behavior	Symmetric
Suppressed	No
Advanced	
Formulation	Pure Penalty
Normal Stiffness	Program Controlled
Update Stiffness	Never
Thermal Conductance	Program Controlled
Pinball Region	Program Controlled

TABLE 12
Orientation 4.1 > Connections > Contact Regions

Object Name	Contact Region 11	Contact Region 12	Contact Region 13	Contact Region 14	Contact Region 15
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face		4 Faces		1 Face
Target	1 Face		4 Faces		1 Face
Contact Bodies	Left Endplate Downstream Hole area		Right Endplate Upstream Hole area		
Target Bodies	Left Endplate Inner Steel slice	Left Endplate Outer Steel slice	Right Endplate Aluminum Casing	Right Endplate Polyurethane	Right Endplate Outer Steel slice
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				
Normal Stiffness	Program Controlled				
Update Stiffness	Never				
Thermal Conductance	Program Controlled				
Pinball Region	Program Controlled				

TABLE 13
Orientation 4.1 > Connections > Contact Regions

Object Name	Contact Region 16	Contact Region 17	Contact Region 18	Contact Region 19	Contact Region 20
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face		4 Faces		1 Face
Target	1 Face		4 Faces		1 Face
Contact Bodies	Right Endplate Upstream Hole area	Left Endplate Upstream Hole area			
Target Bodies	Right Endplate Inner Steel Slice	Left Endplate Aluminum Casing	Left Endplate Polyurethane	Left Endplate Inner Steel slice	Left Endplate Outer Steel slice
Definition					
Type	Bonded				

Scope Mode	Automatic
Behavior	Symmetric
Suppressed	No
Advanced	
Formulation	Pure Penalty
Normal Stiffness	Program Controlled
Update Stiffness	Never
Thermal Conductance	Program Controlled
Pinball Region	Program Controlled

TABLE 14
Orientation 4.1 > Connections > Contact Regions

Object Name	<i>Contact Region 21</i>	<i>Contact Region 22</i>	<i>Contact Region 23</i>	<i>Contact Region 24</i>	<i>Contact Region 25</i>
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	4 Faces	1 Face			
Target	4 Faces	1 Face			
Contact Bodies	Left Endplate Aluminum Casing				
Target Bodies	Left Endplate Polyurethane	Left Endplate Inner Steel slice	Left Endplate Outer Steel slice	Rod 4	Rod 5
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				
Normal Stiffness	Program Controlled				
Update Stiffness	Never				
Thermal Conductance	Program Controlled				
Pinball Region	Program Controlled				

TABLE 15
Orientation 4.1 > Connections > Contact Regions

Object Name	<i>Contact Region 26</i>	<i>Contact Region 27</i>	<i>Contact Region 28</i>	<i>Contact Region 29</i>	<i>Contact Region 30</i>
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face				2 Faces
Target	1 Face				2 Faces
Contact Bodies	Left Endplate Aluminum Casing				
Target Bodies	Rod 6	Rod 1	Rod 2	Rod 3	Hexcel
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				

Advanced	
Formulation	Pure Penalty
Normal Stiffness	Program Controlled
Update Stiffness	Never
Thermal Conductance	Program Controlled
Pinball Region	Program Controlled

TABLE 16
Orientation 4.1 > Connections > Contact Regions

Object Name	<i>Contact Region 31</i>	<i>Contact Region 32</i>	<i>Contact Region 33</i>	<i>Contact Region 34</i>	<i>Contact Region 35</i>
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face		4 Faces		1 Face
Target	1 Face		4 Faces		1 Face
Contact Bodies	Left Endplate Polyurethane			Right Endplate Downstream Hole area	
Target Bodies	Left Endplate Inner Steel slice	Left Endplate Outer Steel slice	Hexcel	Right Endplate Polyurethane	Right Endplate Outer Steel slice
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				
Normal Stiffness	Program Controlled				
Update Stiffness	Never				
Thermal Conductance	Program Controlled				
Pinball Region	Program Controlled				

TABLE 17
Orientation 4.1 > Connections > Contact Regions

Object Name	<i>Contact Region 36</i>	<i>Contact Region 37</i>	<i>Contact Region 38</i>	<i>Contact Region 39</i>	<i>Contact Region 40</i>
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face	4 Faces		1 Face	
Target	1 Face	4 Faces		1 Face	
Contact Bodies	Right Endplate Downstream Hole area	Right Endplate Aluminum Casing			
Target Bodies	Right Endplate Inner Steel Slice	Right Endplate Polyurethane	Right Endplate Outer Steel slice	Right Endplate Inner Steel Slice	Rod 4
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				

Advanced	
Formulation	Pure Penalty
Normal Stiffness	Program Controlled
Update Stiffness	Never
Thermal Conductance	Program Controlled
Pinball Region	Program Controlled

TABLE 18
Orientation 4.1 > Connections > Contact Regions

Object Name	<i>Contact Region 41</i>	<i>Contact Region 42</i>	<i>Contact Region 43</i>	<i>Contact Region 44</i>	<i>Contact Region 45</i>
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face				
Target	1 Face				
Contact Bodies	Right Endplate Aluminum Casing				
Target Bodies	Rod 5	Rod 6	Rod 1	Rod 2	Rod 3
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				
Normal Stiffness	Program Controlled				
Update Stiffness	Never				
Thermal Conductance	Program Controlled				
Pinball Region	Program Controlled				

TABLE 19
Orientation 4.1 > Connections > Contact Regions

Object Name	<i>Contact Region 46</i>	<i>Contact Region 47</i>	<i>Contact Region 48</i>	<i>Contact Region 49</i>	<i>Contact Region 50</i>
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	2 Faces	1 Face			
Target	2 Faces	1 Face			
Contact Bodies	Right Endplate Aluminum Casing	Right Endplate Polyurethane			Left Endplate Inner Steel slice
Target Bodies	Hexcel	Right Endplate Outer Steel slice	Right Endplate Inner Steel Slice	Hexcel	
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				

Normal Stiffness	Program Controlled
Update Stiffness	Never
Thermal Conductance	Program Controlled
Pinball Region	Program Controlled

TABLE 20
Orientation 4.1 > Connections > Contact Regions

Object Name	Contact Region 51	Contact Region 52	Contact Region 53	Contact Region 54	Contact Region 55
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face	4 Faces	1 Face		2 Faces
Target	1 Face	4 Faces	1 Face		2 Faces
Contact Bodies	Right Endplate Inner Steel Slice	Backplate Aluminum Casing			
Target Bodies	Hexcel	Backplate Polyurethane	Backplate Outer steel slice	Back Plate Inner Steel slice	Left Hinge
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				
Normal Stiffness	Program Controlled				
Update Stiffness	Never				
Thermal Conductance	Program Controlled				
Pinball Region	Program Controlled				

TABLE 21
Orientation 4.1 > Connections > Contact Regions

Object Name	Contact Region 56	Contact Region 57	Contact Region 58	Contact Region 59	Contact Region 60
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	2 Faces	1 Face			
Target	2 Faces	1 Face			
Contact Bodies	Backplate Aluminum Casing		Backplate Polyurethane		
Target Bodies	Right Hinge	Hexcel	Backplate Outer steel slice	Back Plate Inner Steel slice	Left Hinge
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				
Normal Stiffness	Program Controlled				

Update Stiffness	Never
Thermal Conductance	Program Controlled
Pinball Region	Program Controlled

TABLE 22
Orientation 4.1 > Connections > Contact Regions

Object Name	Contact Region 61	Contact Region 62	Contact Region 63	Contact Region 64	Contact Region 65
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Contact	1 Face				
Target	1 Face				
Contact Bodies	Backplate Polyurethane		Backplate Outer steel slice		Back Plate Inner Steel slice
Target Bodies	Right Hinge	Hexcel	Left Hinge	Right Hinge	Hexcel
Definition					
Type	Bonded				
Scope Mode	Automatic				
Behavior	Symmetric				
Suppressed	No				
Advanced					
Formulation	Pure Penalty				
Normal Stiffness	Program Controlled				
Update Stiffness	Never				
Thermal Conductance	Program Controlled				
Pinball Region	Program Controlled				

TABLE 23
Orientation 4.1 > Connections > Contact Regions

Object Name	<i>Bonded - Backplate Aluminum Casing To Right Endplate Aluminum Casing</i>	<i>Bonded - Backplate Aluminum Casing To Left Endplate Aluminum Casing</i>
State	Fully Defined	
Scope		
Scoping Method	Geometry Selection	
Contact	1 Edge	
Target	1 Edge	
Contact Bodies	Backplate Aluminum Casing	
Target Bodies	Right Endplate Aluminum Casing	Left Endplate Aluminum Casing
Definition		
Type	Bonded	
Scope Mode	Manual	
Suppressed	No	
Advanced		
Formulation	Pure Penalty	
Normal Stiffness	Program Controlled	
Update Stiffness	Never	
Thermal Conductance	Program Controlled	
Pinball Region	Radius	

Pinball Radius	100. mm
----------------	---------

Mesh

TABLE 24
Orientation 4.1 > Mesh

Object Name	<i>Mesh</i>
State	Solved
Defaults	
Physics Preference	Mechanical
Relevance	-35
Advanced	
Relevance Center	Coarse
Element Size	Default
Shape Checking	Standard Mechanical
Solid Element Midside Nodes	Program Controlled
Straight Sided Elements	No
Initial Size Seed	Active Assembly
Smoothing	Low
Transition	Fast
Statistics	
Nodes	160363
Elements	26466

Static Structural

TABLE 25
Orientation 4.1 > Analysis

Object Name	<i>Static Structural</i>
State	Fully Defined
Definition	
Physics Type	Structural
Analysis Type	Static Structural
Options	
Reference Temp	22. °C

TABLE 26
Orientation 4.1 > Static Structural > Analysis Settings

Object Name	<i>Analysis Settings</i>
State	Fully Defined
Step Controls	
Number Of Steps	1.
Current Step Number	1.
Step End Time	1. s
Auto Time Stepping	Program Controlled
Solver Controls	
Solver Type	Direct
Weak Springs	Program Controlled
Large Deflection	Off
Inertia Relief	Off

Nonlinear Controls	
Force Convergence	Program Controlled
Moment Convergence	Program Controlled
Displacement Convergence	Program Controlled
Rotation Convergence	Program Controlled
Line Search	Program Controlled
Output Controls	
Calculate Stress	Yes
Calculate Strain	Yes
Calculate Results At	All Time Points
Analysis Data Management	
Solver Files Directory	C:\Documents and Settings\Jinnuri\Desktop\website\AI slit\New Constraints\Analysis 3 \Analysis 3 Simulation Files\Static Structural\
Future Analysis	None
Save ANSYS db	No
Delete Unneeded Files	Yes
Nonlinear Solution	No

FIGURE 1
Orientation 4.1 > Static Structural > Figure




TABLE 27
Orientation 4.1 > Static Structural > Accelerations

Object Name	<i>Acceleration</i>
State	Fully Defined
Scope	
Geometry	All Bodies
Definition	
Define By	Vector
Magnitude	9810. mm/s ² (ramped)
Direction	Defined
Suppressed	No

FIGURE 2
Orientation 4.1 > Static Structural > Acceleration




TABLE 28
Orientation 4.1 > Static Structural > Loads

Object Name	<i>Hinge A</i>	<i>Hinge B</i>	<i>Noseplate Face Area</i>	<i>Right Upstream</i>	<i>Right Downstream</i>
State	Fully Defined				
Scope					
Scoping Method	Geometry Selection				
Geometry	5 Faces		1 Face		
Definition					
Define By	Components				
Type	Displacement			Force	
X Component	0. mm (ramped)	Free		-1503.7 N (ramped)	
Y Component	Free	0. mm (ramped)		-158.05 N (ramped)	158.05 N (ramped)
Z Component	0. mm (ramped)			0. N (ramped)	
Suppressed	No				

FIGURE 3
Orientation 4.1 > Static Structural > Hinge A




FIGURE 4
Orientation 4.1 > Static Structural > Hinge B




FIGURE 5
Orientation 4.1 > Static Structural > Noseplate Face Area




FIGURE 6
Orientation 4.1 > Static Structural > Right Upstream




FIGURE 7
Orientation 4.1 > Static Structural > Right Downstream




TABLE 29
Orientation 4.1 > Static Structural > Loads

Object Name	<i>Left Upstream</i>	<i>Left Downstream</i>
State	Fully Defined	
Scope		
Scoping Method	Geometry Selection	
Geometry	1 Face	
Definition		
Define By	Components	
Type	Force	
X Component	1503.7 N (ramped)	
Y Component	158.05 N (ramped)	-158.05 N (ramped)
Z Component	0. N (ramped)	
Suppressed	No	

FIGURE 8
Orientation 4.1 > Static Structural > Left Upstream





FIGURE 9
Orientation 4.1 > Static Structural > Left Downstream



Solution

TABLE 30
Orientation 4.1 > Static Structural > Solution

Object Name	<i>Solution</i>
State	Solved
Adaptive Mesh Refinement	
Max Refinement Loops	1.
Refinement Depth	2.

TABLE 31
Orientation 4.1 > Static Structural > Solution > Solution Information

Object Name	<i>Solution Information</i>
State	Solved
Solution Information	
Solution Output	Solver Output
Newton-Raphson Residuals	0
Update Interval	2.5 s
Display Points	All

TABLE 32
Orientation 4.1 > Static Structural > Solution > Results

Object Name	<i>Total Deformation</i>	<i>X - Directional Deformation</i>	<i>Y - Directional Deformation</i>	<i>Z - Directional Deformation</i>	<i>Equivalent Stress</i>
State	Solved				
Scope					
Geometry	All Bodies				
Definition					
Type	Total Deformation	Directional Deformation			Equivalent (von-Mises) Stress
Display Time	End Time				
Orientation		X Axis	Y Axis	Z Axis	
Shell					Top/Bottom
Results					
Minimum	1.1461e-002 mm	-3.2847e-003 mm	-7.0477e-002 mm	-4.3375e-002 mm	1.4158e-005 MPa
Maximum	0.10761 mm	0.10721 mm	3.2606e-002 mm	9.5021e-003 mm	3.9841 MPa
Minimum Occurs On	Right Hinge	Left Hinge	Left Endplate Outer Steel slice	Hexcel	Right Hinge
Maximum Occurs On	Left Endplate Aluminum Casing		Right Endplate Aluminum Casing	Backplate Outer steel slice	Nose Plate
Information					
Time	1. s				
Load Step	1				
Substep	1				
Iteration Number	1				

FIGURE 10
Orientation 4.1 > Static Structural > Solution > Total Deformation > Figure




FIGURE 11
Orientation 4.1 > Static Structural > Solution > X - Directional Deformation > Figure




FIGURE 12
Orientation 4.1 > Static Structural > Solution > Y - Directional Deformation > Figure




FIGURE 13
Orientation 4.1 > Static Structural > Solution > Z - Directional Deformation > Figure




FIGURE 14
Orientation 4.1 > Static Structural > Solution > Equivalent Stress > Figure





TABLE 33
Orientation 4.1 > Static Structural > Solution > Results

Object Name	Equivalent Elastic Strain
State	Solved
Scope	
Geometry	All Bodies
Definition	
Type	Equivalent (von-Mises) Elastic Strain
Shell	Top/Bottom
Display Time	End Time
Results	
Minimum	1.7814e-008 mm/mm
Maximum	4.9765e-004 mm/mm
Minimum Occurs On	60 Deg Ref line
Maximum Occurs On	Left Hinge
Information	
Time	1. s
Load Step	1
Substep	1
Iteration Number	1

FIGURE 15

Orientation 4.1 > Static Structural > Solution > Equivalent Elastic Strain > Figure



Material Data

Aluminum

TABLE 34
Aluminum > Constants

Structural	
Young's Modulus	68900 MPa
Poisson's Ratio	0.33
Density	2.7e-006 kg/mm ³
Thermal Expansion	2.3e-005 1/°C
Thermal	
Thermal Conductivity	0. W/mm·°C
Specific Heat	0. J/kg·°C
Electromagnetics	
Relative Permeability	0.
Resistivity	0. Ohm-mm

Polyurethane

TABLE 35
Polyurethane > Constants

Structural	
Young's Modulus	66. MPa
Poisson's Ratio	0.3
Density	2.4e-007 kg/mm ³
Thermal Expansion	6.12e-005 1/°C
Thermal	
Thermal Conductivity	0. W/mm·°C
Specific Heat	0. J/kg·°C
Electromagnetics	
Relative Permeability	0.
Resistivity	0. Ohm·mm

Stainless Steel

TABLE 36
Stainless Steel > Constants

Structural	
Young's Modulus	1.93e+005 MPa
Poisson's Ratio	0.3
Density	8.e-006 kg/mm ³
Thermal Expansion	0. 1/°C
Thermal	
Thermal Conductivity	0. W/mm·°C
Specific Heat	0. J/kg·°C
Electromagnetics	
Relative Permeability	0.
Resistivity	0. Ohm·mm

Carbon Fiber

TABLE 37
Carbon Fiber > Constants

Structural	
Young's Modulus	1.5e+005 MPa
Poisson's Ratio	0.3
Density	5.8e-007 kg/mm ³
Thermal Expansion	0. 1/°C
Thermal	
Thermal Conductivity	0. W/mm·°C
Specific Heat	0. J/kg·°C
Electromagnetics	
Relative Permeability	0.
Resistivity	0. Ohm·mm

Hexcel

TABLE 38
Hexcel > Constants

Structural	

Young's Modulus	1.4805e+005 MPa
Poisson's Ratio	0.33
Density	2.8833e-008 kg/mm ³
Thermal Expansion	0. 1/°C
Thermal	
Thermal Conductivity	0. W/mm·°C
Specific Heat	0. J/kg·°C
Electromagnetics	
Relative Permeability	0.
Resistivity	0. Ohm·mm