

Standard Thickness, Tolerance and Panel Size in (mm)

HIGH FREQUENCY LAMINATES			
PRODUCT	STANDARD DIELECTRIC THICKNESS (WITHOUT THE CLADDING)	STANDARD CLADDINGS	STANDARD PANEL SIZES
RT/duroid® 5870 RT/duroid 5880	0.005" (0.127mm) ± 0.0005" 0.010" (0.254mm) ± 0.0007" 0.020" (0.508mm) ± 0.001" 0.031" (0.787mm) ± 0.001" 0.062" (1.570mm) ± 0.002" 0.125" (3.170mm) ± 0.004"	¼, ½, 1, 2 oz EDC, (8.5, 18, 35, 70 µm EDC) ½, 1, 2 oz Rolled CU (18, 35, 70 µm Rolled CU) 5 µm EDC foil is available on thin .005 - 0.020" thicknesses Thick metal AL, CU, BR	18" X 12" (457mm X 305mm) 18" X 24" (457mm X 610mm) 18" X 36" (457mm X 915mm) 18" X 48" (457mm X 1.219m)
RT/duroid 5880LZ	0.010" (0.256mm) ± 0.001 0.020" (0.508mm) ± 0.001 0.025" (0.625mm) ± 0.001 0.030" (0.762mm) ± 0.002 0.040" (1.026mm) ± 0.002 0.050" (1.270mm) ± 0.003 0.100" (2.540mm) ± 0.004 Other thicknesses available in 10 mil increments.	½, 1 oz EDC (18 µm, 35 µm EDC)	12" X 18" (305 X 457mm) 24" X 18" (610 X 457mm) 24" X 54" (610 X 1.37m)
RT/duroid 6002 RT/duroid 6202	0.010" (0.254mm) ± 0.0007" 0.020" (0.508mm) ± 0.001" 0.030" (0.762mm) ± 0.001" 0.060" (1.524mm) ± 0.002"	¼, ½, 1, 2 oz EDC, (8.5, 18, 35, 70 µm EDC) ½, 1, 2 oz Rolled CU (18, 35, 70 µm Rolled CU) Thick metal AL, CU, BR	18" X 12" (457mm X 305mm) 18" X 24" (457mm X 610mm) 18" X 36" (457mm X 915mm) 18" X 48" (457mm X 1.219m)
RT/duroid 6006 RT/duroid 6010LM	0.005" (0.127mm) ± 0.0005" 0.010" (0.254mm) ± 0.0007" 0.025" (0.635mm) ± 0.001" 0.050" (1.270mm) ± 0.002" 0.075" (1.905mm) ± 0.004" 0.100" (2.540mm) ± 0.005"	¼, ½, 1, 2 oz EDC (8.5, 18, 35, 70 µm EDC) ½, 1, 2 oz Rolled CU (17, 35, 70 µm Rolled CU) 5 µm EDC foil is available on RT/duroid 6010.2LM 0.025" thickness Thick metal AL, CU, BR	18" X 12" (457mm X 305mm) not available in 0.010" (0.254mm) 18" X 24" (457 X 610mm) not available in 0.010" (0.254mm) 10" X 10" (254mm X 254mm) 10" X 20" (254mm X 508mm) 20" X 20" (508mm X 508mm)
TMM® 3 TMM 4	0.015" (0.381mm) ± 0.0015" 0.020" (0.508mm) ± 0.0015" 0.030" (0.762mm) ± 0.0015" 0.060" (1.524mm) ± 0.0015" 0.125" (3.175mm) ± 0.0015"	¼, ½, 1, 2 oz EDC (8.5, 18, 35, 70 µm EDC) Thick metal AL, BR	18" X 12" (457mm X 305mm) 18" X 24" (457mm X 610mm)
TMM 6 TMM 10 TMM 10i TMM 13i	0.015" (0.381mm) ± 0.0015" 0.025" (0.635mm) ± 0.0015" 0.050" (1.270mm) ± 0.0015" 0.075" (1.905mm) ± 0.0015" 0.100" (2.540mm) ± 0.0015"	¼, ½, 1, 2 oz EDC (8.5, 18, 35, 70 µm EDC) Thick metal AL, BR	18" X 12" (457mm X 305mm) 18" X 24" (457mm X 610mm)
ULTRALAM® 2000	0.004" (0.101mm) ± 0.0004 0.0101" (0.256mm) ± 0.0009 0.0147" (0.373mm) ± 0.001 0.0190" (0.482mm) ± 0.001 0.030" (0.762mm) ± 0.001 0.060" (1.524mm) ± 0.002	½, 1, 2 oz EDC (8.5, 18, 35, 70 µm EDC) ½, 1, 2 oz Rolled CU (18, 35, 70 µm Rolled CU)	18" X 12" (457 X 305mm) 18" X 24" (457 X 610mm) 18" X 36" (457 X 915mm) 18" X 48" (457 X 1.219m)
ULTRALAM 3850	0.001" (0.025mm) ± 12.5% 0.002" (0.051mm) ± 12.5% 0.004" (0.101mm) ± 12.5%	½, 1 oz (18, 35 µm) EDC 9, 12 µm very low profile reverse treat EDC foil	18" X 12" (457mm X 305mm) 18" X 24" (457mm X 610mm)
XT/duroid™	0.002" (0.051mm) ± 12.5%	½ (18 µm) very low profile reverse treat EDC foil	18" X 12" (457mm X 305mm) 18" X 24" (457mm X 610mm)

Standard Thickness, Tolerance and Panel Size in (mm)

HIGH FREQUENCY LAMINATES			
PRODUCT	STANDARD DIELECTRIC THICKNESS (WITHOUT THE CLADDING)	STANDARD CLADDINGS	STANDARD PANEL SIZES
RO2808™	0.0013 (0.025mm)	½ oz, (18 µm) EDC	18" X 12" (457mm X 305 mm) 20" X 16" (506mm X 405mm)
RO3003™ RO3035™ *RO3203™ *not available in 0.005" (0.127mm)	0.005" (0.127mm) ± 0.0005" 0.010" (0.254mm) ± 0.0007" 0.020" (0.508mm) ± 0.001" 0.030" (0.762mm) ± 0.0015" 0.060" (1.524mm) ± 0.003"	½, 1, 2 oz EDC (18, 35, 70 µm EDC) ½,1,2 oz Rolled CU (18, 35, 70 µm Rolled CU)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
RO3006™ RO3010™ *RO3206™ *RO3210™ *not available in 0.005" (0.127mm) and 0.010" (0.254mm)	0.005" (0.127mm) ± 0.0005" 0.010" (0.254mm) ± 0.0007" 0.025" (0.635mm) ± 0.001" 0.050" (1.270mm) ± 0.002"	½, 1, 2 oz EDC (18, 35, 70 µm EDC) ½,1,2 oz Rolled CU (18, 35, 70 µm Rolled CU)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
*RO4003C™ RO4360™	0.008" (0.203mm) ± 0.001" 0.012" (0.305mm) ± 0.001" 0.016" (0.406mm) ± 0.0015" 0.020" (0.508mm) ± 0.0015" 0.032" (0.813mm) ± 0.002" 0.060" (1.524mm) ± 0.004"	½, 1, 2 oz EDC (18, 35, 70 µm EDC) *½, 1 oz. LoPro™ Reverse Treated EDC Foil (18, 35 µm LoPro Reverse Treated EDC Foil)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
RO4350B™	0.0040" (0.101mm) ± 0.0007" 0.0066" (0.168mm) ± 0.0007" 0.010" (0.254mm) ± 0.001" 0.0133" (0.338mm) ± 0.0015" 0.0166" (0.422mm) ± 0.0015" 0.020" (0.508mm) ± 0.0015" 0.030" (0.762mm) ± 0.002" 0.060" (1.524mm) ± 0.004"	½, 1, 2 oz EDC(18, 35, 70 µm EDC) ½, 1 oz. LoPro Reverse Treated EDC Foil (18, 35 µm LoPro Reverse Treated EDC Foil)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
SYRON™ 7000	0.002" (0.051mm)± 12.5%	½ (18 µm) very low profile reverse treat EDC foil	18" X 12" (457mm X 305mm) 18" X 24" (457mm X 610mm)
BONDING FILM AND BOND-PLY			
3001 Bonding Film Thermoplastic	.0015" (0.038 mm)	N/A	12" X 50' Roll (304 mm X 152.4 m)
ULTRALAM 3908 (LCP) Bond-Ply	.001" (0.025mm) .002" (0.051mm)	N/A	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm)
RO3003 Bond-Ply	.005" (0.127mm)	N/A	25.5" X18"
RO3010 Bond-Ply	.005" (0.127mm)	N/A	20" X 26"
RO4403™ Bond-Ply	.004" (0.102mm)	N/A	12" X 18" (305mm X 457mm)
RO4450B™ Bond-Ply	.0036" (0.091mm) .004" (0.102mm)	N/A	24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
RO4450F™ Bond-Ply	.004" (0.102mm)	N/A	

Standard Thickness, Tolerance and Panel Size in (mm)

ANTENNA GRADE LAMINATES

RO3730™	0.005" (0.127mm) ± 0.0005" 0.010" (0.254mm) ± 0.0007" 0.020" (0.508mm) ± 0.001" 0.030" (0.762mm) ± 0.0015" 0.060" (1.524mm) ± 0.003"	1 oz. Rolled CU (35 µm Rolled CU)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
RO4533™	0.030" (0.762mm) ± 0.002" 0.040" (1.016mm) ± 0.002" 0.060" (1.524mm) ± 0.004"	½, 1 oz EDC (18, 35 µm EDC)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
	0.0307" (0.762mm) ± 0.002" 0.0407" (1.016mm) ± 0.002" 0.0607" (1.524mm) ± 0.004"	½, 1 oz. LoPro Reverse treated EDC foil (18, 35 µm LoPro Reverse treated EDC foil)	
RO4534™	0.032" (0.813mm) ± 0.002" 0.040" (1.016mm) ± 0.002" 0.060" (1.524mm) ± 0.004"	½, 1 oz EDC (18, 35 µm EDC)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
	0.0327" (0.813mm) ± 0.002" 0.0407" (1.016mm) ± 0.002" 0.0607" (1.524mm) ± 0.004"	½, 1 oz. LoPro Reverse treated EDC foil (18, 35 µm LoPro Reverse treated EDC foil)	
RO4535™	0.030" (0.762mm) ± 0.002" 0.040" (1.016mm) ± 0.002" 0.060" (1.524mm) ± 0.004"	½, 1 oz EDC (18, 35 µm EDC)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)
RO4730™	0.0327" (0.813mm) ± 0.002" 0.0607" (1.524mm) ± 0.004"	½, 1 oz. LoPro Reverse treated EDC foil (18, 35 µm LoPro Reverse treated EDC foil)	12" X 18" (305mm X 457mm) 24" X 18" (610mm X 457mm) 48" X 36" (1.220m X 914mm)

Other thicknesses and panel sizes may be available. Contact customer service or one of our international offices for more information.

CONTACT INFORMATION:

USA:	Rogers Advanced Circuit Materials, ISO 9002 certified	Tel: 480-961-1382	Fax: 480-961-4533
Belgium:	Rogers BVBA - Belgium	Tel: 32-9-2353611	Fax: 32-9-2353658
Japan:	Rogers Japan Inc.	Tel: 81-3-5200-2700	Fax: 81-3-5200-0571
Taiwan:	Rogers Taiwan Inc.	Tel: 886-2-86609056	Fax: 886-2-86609057
Korea:	Rogers Korea Inc.	Tel: 82-31-716-6112	Fax: 82-31-716-6208
Singapore:	Rogers Technologies Singapore Inc.	Tel: 65-747-3521	Fax: 65-747-7425
China:	Rogers (Shanghai) International Trading Co., Ltd (Shanghai Office)	Tel: 86-21-62175599	Fax: 86-21-62677913
China:	Rogers (Shanghai) International Trading Co., Ltd (Beijing Office)	Tel: 86-10-5820-7667	Fax: 86-10-5820-7997
China:	Rogers International Trading Co., Ltd (Shenzhen Office)	Tel: 86-755-8236-6060	Fax: 86-755-8236-6123

The information contained in this Product Selector Guide is intended to assist you in designing with Rogers' laminates. It is not intended to and does not create any warranties, express or implied, including any warranty of merchantability or fitness for a particular application. The user should determine the suitability of Rogers' circuit materials for each application.

These commodities, technology and software are exported from the United States in accordance with the Export Administration regulations. Diversion contrary to U.S. law prohibited.

RT/duroid® ULTRALAM®, TMM®, RO3000®, RO4000®, RO4003, RO4350B, RO4450B, RO4450F, RO4533, RO4534, RO4535, RO4730, RO3003, RO2808, RO3006, 3010, RO3035, RO3203, RO3206, RO3210, RO3730, LoPro, SYRON and XT/duroid are licensed trademarks of Rogers Corporation.

© 2009 Rogers Corporation, Printed in U.S.A